

Data Sheet
Date Prepared:

RANDOM PP R370Y

Yuplene R370Y is random polypropylene that is made for injection molding. It has high impact strength and excellent transparency. Since it has high fluidity and dimensional stability, it can be used for food packaging, packaging container, and disposable syringe and various home appliances. Yuplene R370Y complies with FDA regulation in 21 CFR 178.2010 for food packaging substances with adequate additives and contains no dangerous substances according to Federal Regulations in 21 CFR 177.1520.

Application / Use Case

Injection Molding / food container, home appliances, transparent container

Specification

	Specification	Unit	Test Method
Melt Index	18.0	g/10min	ASTM D1238

Physical Properties

	Value	Unit	Test Method
Softening Point(Vicat)	135	g/10min	ASTM D1238
Tensile Strength at Yield	320	°C	ASTM D1525
Elongation at Break	>500	kg/cm²	ASTM D638
IZOD Impact Strength(Notched, 23°C)	6.0	%	ASTM D638
Haze	10	kg-cm/cm	ASTM D256

Head Office 99 Seorin-dong, Jongno-gu, Seoul 110-110, Korea

Tel. 82-2-2121-5114 Fax. 82-2-2121-7001

SK Institute of 140-1 Woncheon-dong, Yuseong-gu, Taejeon, Korea Technology Tel. 82-42-866-7624 Fax. 82-42-866-7603
Online SK energy co., ltd.: www.SKenergy.com

Chemical Business: www.skchem.com

ISO 9001 Certified





Flexural Modulus	>800	%	ASTM D1003
Hardness(Rockwell)	11000	kg/cm²	ASTM D790
Heat Distortion Temperature	85	R Scale	ASTM D785
Accelerated Oven Aging(in Air at 150°C)	94	°C	ASTM D648

These are typical properties only, and are not to be construed as specific limits.

Head Office

SK Institute of Technology Online

99 Seorin-dong, Jongno-gu, Seoul 110-110, Korea Tel. 82-2-2121-5114 Fax. 82-2-2121-7001 140-1 Woncheon-dong, Yuseong-gu, Taejeon, Korea Tel. 82-42-866-7624 Fax. 82-42-866-7603 SK energy co., ltd.: www.SKenergy.com

Chemical Business: www.skchem.com